rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

220V-240V 50/60Hz CRI80 LARA AC RUND Weiß matt 6W IP44

Article nr.: LED54201WW-V2

for indoor use, IP 44 · · housing: die-cast aluminum, glass frosted · housing color: white · not swivelling · beam angle: 95° · power: 6 W · light colour: 3000 K · luminous flux: 519 lm · CRI: >80 · lifespan L70B50: >= 50.000 h · input: 230 V AC · protection class I, MM · · installation depth: 28 mm · installation diameter: 55 mm · outer diameter: 82 mm · energy efficiency class: F · dimmable (please refer to the compatibility list on the homepage) · When used in alternating or cross connection, an LED compensator must be used in · parallel with the switching wire

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094042015
Housing colour	Weiss matt
Height	24.00 mm
Outer diameter	82 mm
Hole size	55 mm
Depth in ceiling	28.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	519.00 lm
Lamp	including LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

220V-240V 50/60Hz CRI80 LARA AC RUND Weiß matt 6W IP44

Article nr.: LED54201WW-V2

TECHNICAL DATA

IP rating	44
Furniture downlight	1
Power	6 W
Psb	0,00 W
Current mA	26 mA
Voltage	230 V
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	20.000 h
Suitable light source	

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

220V-240V 50/60Hz CRI80 LARA AC RUND Weiß matt 6W IP44

Article nr.: LED54201WW-V2

TECHNICAL DRAWING