



eisengebürstet, RGBWW QILE - 23, 55W

IP43 110° 350mA

Article nr.: 45105

RGBW LED recessed downlight with diffuse lighting surface · for indoor use, IP43 · · housing: diecast aluminum, plastic diffuser white · housing color: iron brushed · not swivelling · beam angle: 110° · power: 23.55 W (white 6.5 W) · light color: 3000K + RGB · luminous flux: 966 lm · luminous flux 3000K: 560 lm · CRI: >80 · lifespan: L70B50: >= 50.000 h · input current: 350 mA DC · · installation depth: 96 mm · ceiling cut-out: 105 mm · outer diameter: 121 mm · energy efficiency class: G · not including LED converter · · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094451053
Housing colour	Eisen-gebürstet
Outer diameter	121 mm
Hole size	105 mm
Depth in ceiling	96.00 mm
LED colour	RGBW 3000K
Lightoutput per fixture	966.00 lm
Lightoutput per LED	26.83 lm
Lamp	including LED





eisengebürstet, RGBWW QILE - 23, 55W
IP43 110° 350mA
Article nr.: 45105

TECHNICAL DATA

IP rating	43
Power	23,55 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	36
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	

