




**220V-240V 50/60Hz CRI80 Scheibe matt
SANYA AC RUND Weiß matt 6WIP40
3000K**

Article nr.: ALU46351WW-V2

for indoor use, IP40 · housing: diecast aluminium (plastic protection plate, diffuse) · housing colour: white · beam angle: 95° · power: 6 W · light colour: 3000 K · luminous flux: 526 lm · CRI: >80 · lifespan L70B50: ≥ 50.000 h · input voltage: 220-240 V AC · protection class I, MM · installation depth: 49 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energy efficiency class: F · dimmable (please refer to the compatibility list on the homepage) · When used in alternating or cross connection, an LED compensator must be used in parallel with the switching wire

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094063515
Housing colour	Weiss matt
Height	39.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	49.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	526.00 lm
Lamp	including LED






**220V-240V 50/60Hz CRI80 Scheibe matt
SANYA AC RUND Weiß matt 6WIP40
3000K**

Article nr.: ALU46351WW-V2

TECHNICAL DATA

IP rating	40
Power	6 W
Psb	0,00 W
Current mA	26 mA
Voltage	230 V
Material	Aluminium
Temperature range	-20 - 50
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	20.000 h
Suitable light source	





220V-240V 50/60Hz CRI80 Scheibe matt
SANYA AC RUND Weiß matt 6WIP40
3000K

Article nr.: ALU46351WW-V2

TECHNICAL DRAWING

