



**TALAN XXS DA108mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
5/7/9W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48500

for indoor use, IP44 · with switchable light colour and power on the converter · housing: diecast aluminium, PMMA cover matt · housing colour: white · not swiveling · beam angle: 110° · power: 5/7/9 W · light colour: 2700/3000/4000 K · luminous flux: 470/670/880 lm · CRI: >80 · lifespan L70B50: >= 45,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 30 mm · ceiling cut out: 108 mm · outer diameter: 118.5 mm · including constant current converter · with connector for plug-and-play-operation with 380 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 113.5 x 35.5 x 23.5 · this product contains a light source of energy efficiency class E · _Driver MOQ 1000 pcs - please add details about quantity to order with reference _TALAN DRIVER 485X_

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094485003
Housing colour	Weiss
Height	18.00 mm
Outer diameter	118 mm
Hole size	108 mm
Depth in ceiling	30.00 mm
LED colour	2700/3000/4000 K umschaltbar
Lightoutput per fixture	880.00 lm
Lamp	including LED





**TALAN XXS DA108mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
5/7/9W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48500

TECHNICAL DATA

IP rating	44
Power	5-9 W
Voltage	220-240 V
Material	Aluminium
Temperature range	-10 - 40
CRI	≥ 80
Lifetime L70B50	45.000 h
Lifetime L90B10	36.000 h
Suitable light source	





**TALAN XXS DA108mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
5/7/9W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48500

TECHNICAL DRAWING

