



**TALAN XS DA155mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
7/9/12W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48501

for indoor use, IP44 · with switchable light colour and power on the converter · housing: diecast aluminium, PMMA cover matt · housing colour: white · not swiveling · beam angle: 110° · power: 7/9/12 W · light colour: 2700/3000/4000 K · luminous flux: 617/885/1136 lm · CRI: >80 · lifespan L70B50: >= 45,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 30 mm · ceiling cut out: 155 mm · outer diameter: 168 mm · including constant current converter · with connector for plug-and-play-operation with 380 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 113.5 x 35.5 x 23.5 · this product contains a light source of energy efficiency class F · _Driver MOQ 1000 pcs - please add details about quantity to order with reference _TALAN DRIVER 485X_

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094485010
Housing colour	Weiss
Height	18.00 mm
Outer diameter	168 mm
Hole size	155 mm
Depth in ceiling	30.00 mm
LED colour	2700/3000/4000 K umschaltbar
Lightoutput per fixture	1136.00 lm
Lamp	including LED





**TALAN XS DA155mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
7/9/12W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48501

TECHNICAL DATA

IP rating	44
Power	7-12 W
Voltage	220-240 V
Material	Aluminium
Temperature range	-10 - 40
CRI	≥ 80
Lifetime L70B50	45.000 h
Lifetime L90B10	36.000 h
Suitable light source	





**TALAN XS DA155mm, Rund-Panel,
Multi-W+Lf, Plug&play starr, rund,
7/9/12W, 27/30/4000K, CRI80-weiss,
IP44**

Article nr.: 48501

TECHNICAL DRAWING

