



LED Downlight TALAN XL, TRIAC, 110°, IP44 weiß, 827/830/840, 16/20/24W, plug&play

Article nr.: 48503-V2

for indoor use, IP44 · with switchable light colour and power on the converter · housing: diecast aluminium, PMMA cover matt · housing colour: white · not swiveling · beam angle: 110° · power: 16/20/24 W · light colour: 2700/3000/4000 K · luminous flux: 1630/2050/2390 lm · CRI: >80 · lifespan L70B50: >= 45,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 30 mm · ceiling cut out: 285 mm · outer diameter: 300 mm · including TRIAC dimmable constant current converter · with connector for plug-and-play-operation with 380 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 115 x 39.2 x 24 · this product contains a light source of energy efficiency class E · _Driver MOQ 1000 pcs - please add details about quantity to order with reference _TALAN DRIVER 485X_

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094485072
Housing colour	Weiss
Height	22.50 mm
Outer diameter	300 mm
Hole size	285 mm
Depth in ceiling	30.00 mm
LED colour	2700/3000/4000 K umschaltbar
Lightoutput per fixture	2390.00 lm
Lamp	including LED





LED Downlight TALAN XL, TRIAC, 110°, IP44 weiß, 827/830/840, 16/20/24W, plug&play

Article nr.: 48503-V2

TECHNICAL DATA

IP rating	44
Power	16-24 W
Psb	0,00 W
Voltage	220-240 V
Material	Aluminium
Temperature range	-25 - 50
CRI	≥ 80
Lifetime L70B50	45.000 h
Lifetime L90B10	36.000 h
Suitable light source	





**LED Downlight TALAN XL, TRIAC, 110°,
IP44 weiß, 827/830/840, 16/20/24W,
plug&play**

Article nr.: 48503-V2

TECHNICAL DRAWING

