



**Quadro 4000K 25° 350mA CRI90 m.Scheibe  
.LED Einbaustr. 8W eisengeb. o.Konverter**  
Article nr.: ALU53395NWOK

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protective glass · housing color: iron brushed · 30° swivelling · beam angle: 25° · power: 8 W · light color: 4000 K · luminous flux: 840 lm · CRI: >90 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III, MM · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer dimensions: 82 x 82 mm · energie efficiency class: E · not included LED converter

**TECHNICAL DATA**

Unit Code	pcs
BAR code	4012094333953
Housing colour	Eisen-gebürstet
Length	82.00 mm
Width	82.00 mm
Height	31.00 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	NW ca. 4000 K
Lightoutput per fixture	840.00 lm





**Quadro 4000K 25° 350mA CRI90 m.Scheibe  
.LED Einbaustr. 8W eisengeb. o.Konverter**  
Article nr.: ALU53395NWOK

**TECHNICAL DATA**

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	50.000 h





**Quadro 4000K 25° 350mA CRI90 m.Scheibe  
.LED Einbaustr. 8W eisengeb. o.Konverter**  
Article nr.: ALU53395NWOK

## TECHNICAL DRAWING

