



Quadro 2700K 25° 350mA CRI90

m.Scheibe LED Einbaustr. 8W

chrommatt.o.Konv.

Article nr.: ALU53399UWWOK

for indoor use, IP 20 · housing: diecast aluminum, glass reflector, protective glass · housing color: chrome matt · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 670 lm · CRI: >90 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III, MM · installation depth: 40 mm · ceiling cut-out: 68 mm · outer dimensions: 82 x 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094532998
Housing colour	Chrom matt
Length	82.00 mm
Width	82.00 mm
Height	31.00 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	670.00 lm





Quadro 2700K 25° 350mA CRI90

m.Scheibe LED Einbaustr. 8W

chrommatt.o.Konv.

Article nr.: ALU53399UWWOK

TECHNICAL DATA

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h





Quadro 2700K 25° 350mA CRI90

m.Scheibe LED Einbaustr. 8W

chrommatt.o.Konv.

Article nr.: ALU53399UWWOK

TECHNICAL DRAWING

