rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



TALU LED-Einbaustrahler 1er Set dimmbar Plug&play schwenk., rund, 350mA, 8W, IP20, 3000K, CRI90 - Weiß

Article nr.: ALU57341WWD

for indoor use, IP20 · · housing: diecast aluminium, glass reflector, protective glass · housing colour: white · 30° swiveling · beam angle: 40° · power: 8 W · light colour: 3.000 K · luminous flux: 715 lm · CRI: >90 · lifespan L70B50: >= 54,000 h · input voltage range: 230 V AC, 50/60 Hz · protection class II · · installation depth: 40 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector for plug-and-play-operation · tool-free replacement of the lamp · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094373416
Housing colour	Weiss
Height	31.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	715.00 lm
Lamp	Inklusive LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



TALU LED-Einbaustrahler 1er Set

dimmbar Plug&play schwenk., rund, 350mA, 8W, IP20, 3000K, CRI90 - Weiß

Article nr.: ALU57341WWD

TECHNICAL DATA

IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	sonstige
Input voltage	230
Output voltage	17-23
Material	Aluminium
Tollerance	6.00
Efficiency	79.00
Temperature range	-20 - 45
CRI	≥ 90
Lifetime L70B50	54.000 h