



**TALU LED-Einbaustrahler ohne  
Konverter schwenk., rund, 350mA, 8W,  
IP20, 2700K, CRI90 - Chrom**  
Article nr.: ALU57344UWWOK

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protective glass · housing color: chrome · 30° swivelling · beam angle: 40° · power: 8 W · light color: 2700 K · luminous flux: 694 lm · CRI: >90 · lifespan L70B50: >= 50,000 h · input: 350 mA DC · protection class III, MM · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energy efficiency class: F · not included LED converter

## TECHNICAL DATA

|                         |                          |
|-------------------------|--------------------------|
| Unit Code               | pcs                      |
| BAR code                | 4012094073446            |
| Housing colour          | Chrom                    |
| Height                  | 31.00 mm                 |
| Outer diameter          | 82 mm                    |
| Hole size               | 68 mm                    |
| Depth in ceiling        | 40.00 mm                 |
| LED colour              | ca. 2700K ultra warmweiß |
| Lightoutput per fixture | 694.00 lm                |
| Lamp                    | including LED            |





**TALU LED-Einbaustrahler ohne  
Konverter schwenk., rund, 350mA, 8W,  
IP20, 2700K, CRI90 - Chrom**  
Article nr.: ALU57344UWWOK

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 20          |
| Power                   | 8 W         |
| Psb                     | 0,00 W      |
| Current mA              | 350 mA      |
| Amount of LED           | 1           |
| Material                | Aluminium   |
| Temperature range       | -20 - 40    |
| Energy efficiency class | EEK-Label_F |
| CRI                     | ≥ 90        |
| Lifetime L70B50         | 50.000 h    |
| Lifetime L90B10         | 46.000 h    |
| Suitable light source   |             |





**TALU LED-Einbaustrahler ohne  
Konverter schwenk., rund, 350mA, 8W,  
IP20, 2700K, CRI90 - Chrom**  
Article nr.: ALU57344UWWOK

## TECHNICAL DRAWING

