




**TALU LED-Einbaustrahler 1er Set
dimmbar Plug&play schwenk., rund,
350mA, 8W, IP20, 3000K, CRI90 -Eisen
geb**

Article nr.: ALU57345WWD

for indoor use, IP20 · housing: diecast aluminium, glass reflector, protective glass · housing colour: brushed iron · 30° swiveling · beam angle: 40° · power: 8 W · light colour: 3.000 K · luminous flux: 715 lm · CRI: >90 · lifespan L70B50: >= 54,000 h · input voltage range: 230 V AC, 50/60 Hz · protection class II · installation depth: 40 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector for plug-and-play-operation · tool-free replacement of the lamp · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094373454
Housing colour	Eisen-gebürstet
Height	31.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	715.00 lm
Lamp	Inklusive LED





TALU LED-Einbaustrahler 1er Set dimmbar Plug&play schwenk., rund, 350mA, 8W, IP20, 3000K, CRI90 -Eisen geb

Article nr.: ALU57345WWD

TECHNICAL DATA

IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	sonstige
Input voltage	230
Output voltage	17-23
Material	Aluminium
Tolerance	6.00
Efficiency	79.00
Temperature range	-20 - 45
CRI	≥ 90
Lifetime L70B50	54.000 h

