rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2300-3000K 40° 350mA CRI90 m.Scheibe LED Einbaustr. 7W schwarz o.Konverter

Article nr.: ALU57352DTWOK-V2

for indoor use, IP 20 · · housing: diecast aluminium, glass reflector, protective glass · housing color: black · 30 ° swiveling · beam angle: 40° · power: 7 W · light color: 2300-3000K DimToWarm · luminous flux: 504 lm · CRI: >90 · lifetime L70B50: >= 55.000 h · input: 350 mA · protection class III · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: G · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094173528
Housing colour	Schwarz
Height	34.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	3000-2300K Dim to Warm
Lightoutput per fixture	504.00 lm
Lamp	including LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2300-3000K 40° 350mA CRI90 m.Scheibe LED Einbaustr. 7W schwarz o.Konverter

Article nr.: ALU57352DTWOK-V2

TECHNICAL DATA

IP rating	20
Power	7 W
Current mA	350 mA
Material	Aluminium
Temperature range	-20 - 40
Energy ffficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	55.000 h
Lifetime L90B10	46.000 h
Suitable light source	



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2300-3000K 40° 350mA CRI90 m.Scheibe LED Einbaustr. 7W schwarz o.Konverter

Article nr.: ALU57352DTWOK-V2

TECHNICAL DRAWING

