



2300-3000K 40° 350mA CRI90

m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.

Article nr.: ALU57355DTWOK-V2

for indoor use, IP 20 · housing: diecast aluminium, glass reflector, protective glass · housing color: brushed iron · 30 ° swiveling · beam angle: 40° · power: 7 W · light color: 2300-3000K DimToWarm · luminous flux: 504 lm · CRI: >90 · lifetime L70B50: >= 55.000 h · input: 350 mA · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: G · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094173559
Housing colour	Eisen-gebürstet
Height	34.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	3000-2300K Dim to Warm
Lightoutput per fixture	504.00 lm
Lamp	including LED





2300-3000K 40° 350mA CRI90


m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.

Article nr.: ALU57355DTWOK-V2

TECHNICAL DATA

IP rating	20
Power	7 W
Current mA	350 mA
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	55.000 h
Lifetime L90B10	46.000 h
Suitable light source	





2300-3000K 40° 350mA CRI90

m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.

Article nr.: ALU57355DTWOK-V2

TECHNICAL DRAWING

