



2000-2800K 40° 350mA CRI80

m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.

Article nr.: ALU57355DTWOK

for indoor use, IP 20 · housing: diecast aluminum, glass reflector, protective glass · housing color: iron-brushed · 30° swivelling · beam angle: 40° · power: 7 W · light color: 2200-2800K DimToWarm · luminous flux: 580 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094071558
Housing colour	Eisen-gebürstet
Height	34.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	2800-2200K Dim to Warm
Lightoutput per fixture	580.00 lm
Lamp	including LED





2000-2800K 40° 350mA CRI80

m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.


Article nr.: ALU57355DTWOK

TECHNICAL DATA

IP rating	20
Power	7 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	



Reihenschaltung





2000-2800K 40° 350mA CRI80

m.Scheibe LED Einbaustr. 7W

eisengebürstet o.Konv.

Article nr.: ALU57355DTWOK

TECHNICAL DRAWING

