



ALUSPIEGEL 40° 350mA CRI90 3000K
TALU POWER 10W Weiß m.Konverter
Article nr.: ALU58271WW

TALU 10 W COB LED recessed downlight · for indoor use, IP20 · · movable, snap ring · housing: diecast aluminium · beam angle: 40° · power: 10 W · light color: 3000 K · luminous flux: 860 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input current: 350 mA · · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 83 mm · inclusive switchable converter · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094483276
Housing colour	Weiss
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	860.00 lm
Lamp	Inklusive LED
IP rating	20






ALUSPIEGEL 40° 350mA CRI90 3000K
TALU POWER 10W Weiß m.Konverter
Article nr.: ALU58271WW

TECHNICAL DATA

Power	10 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 90
Lifetime L70B50	50.000 h





ALUSPIEGEL 40° 350mA CRI90 3000K
TALU POWER 10W Weiß m.Konverter
Article nr.: ALU58271WW

TECHNICAL DRAWING




image not found or type unknown