



ALUSPIEGEL 40° 350mA CRI90 3000K

TALU POWER 10W eisengeb.

o.Konverter

Article nr.: ALU58275WWOK

for indoor use, IP 20 · housing: diecast aluminum, glass reflector · housing color: iron brushed · 30° swivelling · beam angle: 40° · power: 10 W · light color: 3000 K · luminous flux: 860 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · installation depth: 45 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094582757
Housing colour	Eisen-gebürstet
Height	40.00 mm
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	860.00 lm
Lamp	Inklusive LED





ALUSPIEGEL 40° 350mA CRI90 3000K

TALU POWER 10W eisengeb.

o.Konverter

Article nr.: ALU58275WWOK

TECHNICAL DATA

IP rating	20
Power	10 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h



Reihenschaltung





ALUSPIEGEL 40° 350mA CRI90 3000K

TALU POWER 10W eisengeb.

o.Konverter

Article nr.: ALU58275WWOK

TECHNICAL DRAWING




image not found or type unknown