



ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. m.Konv.
 Article nr.: ALU58375WW

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector · housing color: iron brushed · 30° swivelling · beam angle: 40° · power: 10 W · light color: 3000 K · luminous flux: 1180 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input: 350 mA DC · protection class III · · installation depth: 45 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · including LED converter · this product contains a light source of energy efficiency class E

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094483757
Housing colour	Eisen-gebürstet
Height	40.00 mm
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1180.00 lm
Lamp	Inklusive LED






ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. m.Konv.
Article nr.: ALU58375WW

TECHNICAL DATA

IP rating	20
Power	10 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
CRI	≥ 80
Lifetime L70B50	50.000 h





ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. m.Konv.
Article nr.: ALU58375WW

TECHNICAL DRAWING




image not found or type unknown