



ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. o.Konv.
 Article nr.: ALU58375WWOK

for indoor use, IP 20 · housing: diecast aluminum, glass reflector · housing color: iron brushed · 30° swivelling · beam angle: 40° · power: 10 W · light color: 3000 K · luminous flux: 1180 lm · CRI: >80 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · installation depth: 45 mm · ceiling cut-out: 68 mm · outer diameter: 83 mm · energie efficiency class: E · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094583754
Housing colour	Eisen-gebürstet
Height	40.00 mm
Outer diameter	83 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1180.00 lm
Lamp	Inklusive LED





ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. o.Konv.
Article nr.: ALU58375WWOK

TECHNICAL DATA

IP rating	20
Power	10 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h





ALUSPIEGEL 40° 350mA CRI80 3000K
TALU POWER 10W eisengeb. o.Konv.
Article nr.: ALU58375WWOK

TECHNICAL DRAWING

