rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2700K 25° 350mA CRI90 m.Scheibe LED Einbaustr. 8W chrom o.Konv. Spannd.

Article nr.: C57354UWWOK

TALU 8W COB for stretched ceilings LED recessed downlight · for indoor use, IP20 · housing: diecast aluminium, glass reflector, protective glass · movable · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 670 lm · CRI: >90 · lifespan L70B50: >= 50.000 h · input current: 350 mA · exclusive converter · energy efficiency class: F · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094973548
Housing colour	Chrom
Outer diameter	87 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	670.00 lm
Lamp	including LED
IP rating	20



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2700K 25° 350mA CRI90 m.Scheibe LED Einbaustr. 8W chrom o.Konv. Spannd.

Article nr.: C57354UWWOK

TECHNICAL DATA

Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Suitable light source	



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



2700K 25° 350mA CRI90 m.Scheibe LED Einbaustr. 8W chrom o.Konv. Spannd.

Article nr.: C57354UWWOK

TECHNICAL DRAWING

