



**2700K 25° 350mA CRI90 m.Scheibe LED
Einbaustr. 8W chromm.o.Konv. Spannd.**
Article nr.: C57359UWWOK

stretch ceiling downlight · for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protection glass · housing color: chrome matt · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 670 lm · CRI: >90 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer diameter: 87.8 mm · energy efficiency class: F · not included LED converter · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094973593
Housing colour	Gold matt
Outer diameter	87 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	670.00 lm
Lamp	including LED
IP rating	20





2700K 25° 350mA CRI90 m.Scheibe LED
Einbaustr. 8W chromm.o.Konv. Spannd.
Article nr.: C57359UWWOK

TECHNICAL DATA

Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Suitable light source	





2700K 25° 350mA CRI90 m.Scheibe LED
Einbaustr. 8W chromm.o.Konv. Spannd.
Article nr.: C57359UWWOK

TECHNICAL DRAWING

