rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



TULKA starr 1, 4401 X5CrNiMo 316 weiss LED Einbaustr. 8W IP55 o.Konverter

Article nr.: R57691UWWOK

for indoor- and outdoor use, IP 55 · · housing: V4A stainless steel, glass reflector, protective glass · housing color: white · not swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 738 lm · CRI: >80 · lifetime L70B50: >= 54.000 h · input: 350 mA DC · protection class III · · installation depth: 55 mm · ceiling cut-out: 68 mm · outer diameter: 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094476919
Housing colour	Weiss
Height	44.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	55.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	738.00 lm
Lamp	Inklusive LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



TULKA starr 1, 4401 X5CrNiMo 316 weiss LED Einbaustr. 8W IP55 o.Konverter

Article nr.: R57691UWWOK

TECHNICAL DATA

IP rating	55
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Edelstahl
Temperature range	-20 - 40
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	54.000 h



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



TULKA starr 1, 4401 X5CrNiMo 316 weiss LED Einbaustr. 8W IP55 o.Konverter

Article nr.: R57691UWWOK

TECHNICAL DRAWING

