



VARDAflex AC Eco 4000K 10M-Rolle Flex.LED-Strip, 200-240V 50/60Hz IP65

Article nr.: 74918

for outdoor use. · can be separated every 50 cm or 27 LEDs · number of LEDs: 540 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 519 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70: >= 36.000 h · energy efficiency class: A · LxWxH in mm: 10.000 x 15,5 x 6 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · Delivery contents: 10 meter roll, in-feeder connector and an end cap as provided · not dimmable · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094749181
Housing colour	Weiss
Length	10000.00 mm
Width	15.50 mm
Height	6.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	5190.00 lm
Lightoutput per LED	9.62 lm
Lamp	including LED





VARDAflex AC Eco 4000K 10M-Rolle
Flex.LED-Strip, 200-240V 50/60Hz IP65
Article nr.: 74918

TECHNICAL DATA

IP rating	65
Power	80 W
Current mA	348 mA
Amount of LED	540
Input voltage	230
Temperature range	-20 - 40
LED per meter	54
Dimension of segments	500.00 mm
CRI	≥ 90
Lifetime L70B50	36.000 h
Suitable light source	

