



## VARDAflex AC Eco 6000K 50M-Rolle Flex.LED-Strip, 200-240V 50/60Hz IP65

Article nr.: 74924

for outdoor use. · can be separated every 50 cm or 27 LEDs · number of LEDs: 2700 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 545 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70: >= 36.000 h · LxWxH in mm: 50.000 x 15,5 x 6 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · Delivery contents: 50 meter roll, in-feeder connector and an end cap as provided · not dimmable · · SECONDLIFE ITEM -heavily discounted- only while stocks last!

### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | pcs                |
| BAR code                | 4012094749242      |
| Housing colour          | Weiss              |
| Length                  | 50000.00 mm        |
| Width                   | 15.50 mm           |
| Height                  | 6.00 mm            |
| LED colour              | ca. 6000K kaltweiß |
| Lightoutput per fixture | 27250.00 lm        |
| Lightoutput per LED     | 10.10 lm           |
| Lamp                    | including LED      |





**VARDAflex AC Eco 6000K 50M-Rolle**  
**Flex.LED-Strip, 200-240V 50/60Hz IP65**  
Article nr.: 74924

## TECHNICAL DATA

|                       |           |
|-----------------------|-----------|
| IP rating             | 65        |
| Power                 | 400 W     |
| Current mA            | 1740 mA   |
| Amount of LED         | 2700      |
| Input voltage         | 230       |
| Temperature range     | -20 - 40  |
| LED per meter         | 54        |
| Dimension of segments | 500.00 mm |
| CRI                   | ≥ 90      |
| Lifetime L70B50       | 36.000 h  |
| Suitable light source |           |

