



VARDAflex Eco AC 4000K 50M-Rolle Flex.LED-Strip, 230V 50/60Hz IP65

Article nr.: 74938

for indoor and outdoor use, IP65 and UV resistant · can be separated every 250 mm or 14 LEDs · number of LEDs: 2800 · LED pitch: 17.85 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 800 lm · voltage: 230V AC · power per meter: 9 W · lifespan L70B50: >= 35.000 h · energy efficiency class: F · LxWxH in mm: 50,000 x 17 x 13.5 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · Delivery contents: 50 meter roll, in-feeder connector and an end cap as provided · not dimmable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094749389
Housing colour	Weiss
Length	50000.00 mm
Width	17.00 mm
Height	13.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	40000.00 lm
Lightoutput per LED	14.29 lm
Lamp	including LED





VARDAflex Eco AC 4000K 50M-Rolle
Flex.LED-Strip, 230V 50/60Hz IP65
Article nr.: 74938

TECHNICAL DATA

IP rating	65
Power	450 W
Psb	0,00 W
Current mA	1956 mA
Voltage	230 V
Amount of LED	2800
Material	Kunststoff
Temperature range	-20 - 40
LED per meter	56
Dimension of segments	250.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	35.000 h
Lifetime L90B10	10.000 h
Suitable light source	





VARDAflex Eco AC 4000K 50M-Rolle
Flex.LED-Strip, 230V 50/60Hz IP65
Article nr.: 74938

TECHNICAL DRAWING

