



VARDAflex AC Work Light 4000K - 25M- Trommel Vergossener LED-Strip, 230V, 8W/m, IP65, 4000K

Article nr.: 79918

Construction site lighting in LED strip design · for outdoor use, IP65 · UV-resistant · number of LEDs: 1850 · LED pitch: 13.51 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 800 lm · voltage: 230 V AC · power per meter: 8 W · energy efficiency class: E · lifetime L70B50: >= 50,000 h · LxWxH in mm: 25.000 x 11.3 x 8 · Attention: Only operate the LED strip when completely unrolled · Maximum length per connection: 25 meter · Scope of delivery: 25 metre roll wound onto a drum with 1.6 m connection cable and contour plug · Suitable for use on construction sites in accordance with DGUV-I 203-005,K2 + DGUV-I 203-006

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094799186
Housing colour	Weiss
Length	25000.00 mm
Width	11.30 mm
Height	8.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	20000.00 lm
Lightoutput per LED	10.81 lm
Lamp	including LED





**VARDAflex AC Work Light 4000K - 25M-
Trommel Vergossener LED-Strip, 230V,
8W/m, IP65, 4000K**
Article nr.: 79918

TECHNICAL DATA

IP rating	65
Power	200 W
Psb	0,0 W
Voltage	230 V
Amount of LED	1850
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	74
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	28.000 h
Suitable light source	





VARDAflex AC Work Light 4000K - 25M-
Trommel Vergossener LED-Strip, 230V,
8W/m, IP65, 4000K
Article nr.: 79918

TECHNICAL DRAWING

