




VARDAflex AC Work Light+ - 15M Trommel
verlängerbar bis 45m, LED-Strip, 230V,
12W/m, IP65, 3000K, CRI90
 Article nr.: 79925

Construction site lighting in LED strip design · for outdoor use, IP65 · UV-resistant · number of LEDs: 3600 · LED pitch: 8.33 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 1110 lm · voltage: 230 V AC · power per meter: 12 W · energy efficiency class: F · lifetime L70B50: >= 50,000 h · LxWxH in mm: 15.000 x 17 x 7 · Attention: Only operate the LED strip when completely unrolled · Maximum length per connection: 45 meter · Scope of delivery: 15 metre roll wound onto a drum with 1.5 m connection cable with rectifier and · contour plug (CEE7/17) at the beginning and a 0.4 m cable and M15 socket at the end for connecting · to the next VARDAflex AC Work Light+ · Suitable for use on construction sites in accordance with DGUV-I 203-005,K2 + DGUV-I 203-006

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094799254
Housing colour	Weiss
Length	15000.00 mm
Width	17.00 mm
Height	7.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	16650.00 lm
Lightoutput per LED	4.63 lm
Lamp	including LED





VARDAflex AC Work Light+ - 15M Trommel
verlängerbar bis 45m, LED-Strip, 230V,
12W/m, IP65, 3000K, CRI90
Article nr.: 79925

TECHNICAL DATA

IP rating	65
Power	180 W
Psb	0,00 W
Current mA	782 mA
Voltage	230 V
Amount of LED	3600
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	240
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	28.000 h
Suitable light source	





VARDAflex AC Work Light+ - 15M Trommel
verlängerbar bis 45m, LED-Strip, 230V,
12W/m, IP65, 3000K, CRI90
Article nr.: 79925

TECHNICAL DRAWING

