



## VARDAflex Eco AC 3000K Flex.LED-Strip, 230V 50/60Hz IP65

Article nr.: S74935

for indoor and outdoor use, IP65 · UV resistant · can be separated every 250 mm or 14 LEDs · number of LEDs per meter: 56 · LED pitch: 17.85 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 755 lm · voltage: 230V AC · power per meter: 9 W · lifespan L70B50: >= 35.000 h · energy efficiency class: F · WxH in mm: 17 x 13.5 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · non dimmable

### TECHNICAL DATA

|                     |                    |
|---------------------|--------------------|
| Unit Code           | metre              |
| BAR code            | 4012094049359      |
| Housing colour      | Weiss              |
| Width               | 17.00 mm           |
| Height              | 13.50 mm           |
| LED colour          | ca. 3000K warmweiß |
| Lightoutput per LED | 13.48 lm           |
| Lamp                | including LED      |
| IP rating           | 65                 |
| Psb                 | 0,00 W             |





**VARDAflex Eco AC 3000K Flex.LED-Strip, 230V 50/60Hz IP65**  
Article nr.: S74935

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| Voltage                 | 230 V       |
| Material                | Kunststoff  |
| Temperature range       | -20 - 40    |
| LED per meter           | 56          |
| Dimension of segments   | 250.00 mm   |
| Energy efficiency class | EEK-Label_F |
| CRI                     | ≥ 90        |
| Lifetime L70B50         | 35.000 h    |
| Lifetime L90B10         | 10.000 h    |
| Suitable light source   |             |





**VARDAflex Eco AC 3000K Flex.LED-Strip, 230V 50/60Hz IP65**  
Article nr.: S74935

## TECHNICAL DRAWING

