rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 AC, IP65 230V, 9W/m, 940, lfm

Article nr.: S74938

for indoor and outdoor use, IP65 · UV resistant · can be seperated every 250 mm or 14 LEDs · number of LEDs per meter: 56 · LED pitch: 17.85 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 800 lm · voltage: 230V AC · power per meter: 9 W · lifespan L70B50: >= 35.000 h · energy efficiency class: F · WxH in mm: 17 x 13.5 · · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · non dimmable

TECHNICAL DATA

Unit Code	metre
BAR code	4012094049380
Housing colour	Weiss
Width	17.00 mm
Height	13.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per LED	14.29 lm
Lamp	including LED
IP rating	65
Psb	0,00 W

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 AC, IP65 230V, 9W/m, 940, lfm

Article nr.: S74938

TECHNICAL DATA

Voltage	230 V
Material	Kunststoff
Temperature range	-20 - 40
LED per meter	56
Dimension of segments	250.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	35.000 h
Lifetime L90B10	10.000 h
Suitable light source	

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 AC, IP65 230V, 9W/m, 940, lfm

Article nr.: S74938

TECHNICAL DRAWING

