



VARDAflex Eco AC 4000K 50M-Rolle Flex.LED-Strip, 200-240V 50/60Hz IP65 Article nr.: 74928-V2

for outdoor use, IP65 and UV resistant · can be separated every 50 cm or 27 LEDs · number of LEDs: 2700 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 633 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70B50: >= 30.000 h · energy efficiency class: G · LxWxH in mm: 50.000 x 15,5 x 6.5 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length. · Delivery contents: 50 meter roll, in-feeder connector and an end cap as provided · not dimmable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094740287
Housing colour	Weiss
Length	50000.00 mm
Width	15.50 mm
Height	6.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	31650.00 lm
Lightoutput per LED	11.72 lm
Lamp	Inklusive LED





VARDAflex Eco AC 4000K 50M-Rolle
Flex.LED-Strip, 200-240V 50/60Hz IP65
Article nr.: 74928-V2

TECHNICAL DATA

IP rating	65
Power	400 W
Current mA	1.739 mA
Voltage	220-240 V
Amount of LED	2700
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	54
Dimension of segments	500.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	30.000 h

