




VARDAflex IP54 - 5M-Rolle Flex.LED-Strip, 24V, 4, 8W, IP54, 4000K

Article nr.: 79488

flexible LED strip extruded with silicone · and self-adhesive back, · for indoor and outdoor use, IP54 · UV-resistant · cuttable every 100 mm / 6 LEDs · number of LEDs: 300 · LED pitch: 16.67 mm · beam angle: 120° · CRI: > 80 · luminous flux per metre: 495 lm · power per metre: 4.8 W · energy efficiency class: E · lifetime L70B50: >= 54,000 h · LxWxH in mm: 5,000 x 8 x 2.5 · Easy solderless installation with optional connectors. · Maximum length per connection: 5 metres. New connection for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094794884
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2475.00 lm
Lightoutput per LED	8.25 lm
Lamp	including LED





VARDAflex IP54 - 5M-Rolle Flex.LED-Strip, 24V, 4, 8W, IP54, 4000K

Article nr.: 79488

TECHNICAL DATA

IP rating	54
Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	300
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	54.000 h
Suitable light source	





**VARDAflex IP54 - 5M-Rolle Flex.LED-
Strip, 24V, 4, 8W, IP54, 4000K**
Article nr.: 79488

TECHNICAL DRAWING

