




VARDAflex Osmium Piko TVQ 2700K - 5M-Rolle LED-Strip, 24V, 13W/m, IP65, 2700K

Article nr.: 79627

flexible LED Stripe sealed in UV- and · saltwater resistant white silicone · for indoor- and outdoor use, IP65 · · cuttable every 50 mm / 7 LEDs · amount of LEDs per meter: 140 · LED pitch: 7.14 mm · beam angle: 110° · CRI: >90 · luminous flux per meter: 590 lm · power per meter: 13 W · lifetime L70B50: >= 54,000 h · LxWxH in mm: 5,000 x 11 x 11 · · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending diameter vertical: 110 mm · Delivery contents: 5 meter reel with 1 meter connection cable on both ends, · 2x silicon end caps · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094797274
Housing colour	Weiss
Length	5000.00 mm
Width	11.00 mm
Height	11.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	2950.00 lm
Lightoutput per LED	4.21 lm
Lamp	including LED





VARDAflex Osmium Piko TVQ 2700K - 5M-Rolle LED-Strip, 24V, 13W/m, IP65, 2700K

Article nr.: 79627

TECHNICAL DATA

IP rating	65
Power	65 W
Psb	0,00 W
Current mA	2708 mA
Voltage	24 V
Amount of LED	700
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
CRI	≥ 90
Lifetime L70B50	54.000 h
Lifetime L90B10	39.000 h
Suitable light source	





**VARDAflex Osmium Piko TVQ 2700K -
5M-Rolle LED-Strip, 24V, 13W/m, IP65,
2700K**

Article nr.: 79627

TECHNICAL DRAWING

