




VARDAflex Eco Plus Profi IP67 - 5 M- Rolle Flex.LED Strip, 24V, 14, 4W/m, IP67, 4000K

Article nr.: 82078

Flexible LED Stripe sealed in transparent UV resistant silicone · for indoor and outdoor use, IP67 · with self adhesive backside · cuttable every 62.5 mm / 8 LEDs · amount of LEDs: 640 · LED pitch: 7.81 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 1513 lm · voltage: 24 V DC · power per meter: 14.4 W · lifespan L70B50: >= 50,000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 12 x 4.6 · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll with 300 mm connection cable, · 10 x mounting bracket

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094820781
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	4.60 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	7565.00 lm
Lightoutput per LED	11.82 lm
Lamp	including LED






VARDAflex Eco Plus Profi IP67 - 5 M- Rolle Flex.LED Strip, 24V, 14, 4W/m, IP67, 4000K

Article nr.: 82078

TECHNICAL DATA

IP rating	67
Power	72 W
Psb	0,0 W
Current mA	3000 mA
Voltage	24 V
Amount of LED	640
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	128
Dimension of segments	62.50 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	28.000 h
Suitable light source	





**VARDAflex Eco Plus Profi IP67 - 5 M-
Rolle Flex.LED Strip, 24V, 14, 4W/m,
IP67, 4000K**

Article nr.: 82078

TECHNICAL DRAWING

