rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 4000K

Article nr.: 82568

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP66 · uv-resistant · · can be seperated every 100 mm or 7 LEDs · number of LEDs: 350 · LED pitch: 14.28 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 410 lm · input: 24V DC · power per meter: 4.8 W · lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 5.000 x 9.2 x 4.4 · · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel with 300 mm connecting cable, · 10 x mounting bracket, 10 x screw

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094825687
Housing colour	Weiss
Length	5000.00 mm
Width	9.20 mm
Height	4.40 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2050.00 lm
Lightoutput per LED	5.86 lm
Lamp	Inklusive LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 4000K

Article nr.: 82568

TECHNICAL DATA

IP rating	66
Power	24 W
Current mA	1.000 mA
Voltage	24 V
Amount of LED	350
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy ffficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	36.000 h

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 4000K

Article nr.: 82568

TECHNICAL DRAWING

