




VARDAflex Quantum COB IP65 - 5m
Flex.LED Strip, 24V, IP65, 2700K, CRI80
 Article nr.: 84567

in heat-shrink tubing with self-adhesive backside, · for indoor and outdoor use, IP65 · not UV-resistant · cuttable every 50 mm or 24 LEDs · number of LEDs: 2400 · LED pitch: 2.08 mm · beam angle: 180° · CRI: >80 · luminous flux per meter: 610 lm · input: 24 V DC · power per meter: 5 W · lifetime L70B50: >= 54.000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 8.4 x 2.3 · Maximum length per connection: 5 meter. New connectors for greater length. · Scope of delivery: 5 metre roll with 300 mm connection cable, · 10x feed shrink tubing, 10x end cap shrink tubing

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094845678
Length	5000.00 mm
Width	8.40 mm
Height	2.30 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	3050.00 lm
Lightoutput per LED	1.27 lm
Lamp	including LED
IP rating	65






VARDAflex Quantum COB IP65 - 5m
Flex.LED Strip, 24V, IP65, 2700K, CRI80
Article nr.: 84567

TECHNICAL DATA

Power	25 W
Psb	0,00 W
Current mA	1042 mA
Voltage	24 V
Amount of LED	2400
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	480
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	54.000 h
Lifetime L90B10	20.000 h
Suitable light source	





VARDAflex Quantum COB IP65 - 5m
Flex.LED Strip, 24V, IP65, 2700K, CRI80
Article nr.: 84567

TECHNICAL DRAWING

