




VARDaflex Standard IP67 Reach25 Flex.LED Strip, 24V, IP67, 3000K

Article nr.: 86550-V3

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP67 · not uv-resistant · ·
can be seperated every 100 mm or 6 LEDs · number of LEDs: 1500 · LED pitch: 16.67 mm · beam
angle: 120° · CRI: >80 · luminous flux per meter: 385 lm · input: 24V DC · power per meter: 3.6 W ·
lifetime L70B50: >= 50,000 h · energy efficiency class: E · LxWxH in mm: 25,000 x 12 x 6 · · Maximum
length per connection: 25 meter. New connectors for greater length. · Delivery contents: 25 metre roll
with 300 mm connection cable, · 100 x mounting bracket made from silicone, 4 x in-feeder cap, · 4x
end cap

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094865515
Housing colour	farblos
Length	25000.00 mm
Width	12.50 mm
Height	6.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	10000.00 lm
Lightoutput per LED	6.67 lm
Lamp	including LED






VARDaflex Standard IP67 Reach25 Flex.LED Strip, 24V, IP67, 3000K

Article nr.: 86550-V3

TECHNICAL DATA

IP rating	67
Power	90 W
Psb	0,00 W
Current mA	3750 mA
Voltage	24 V
Amount of LED	1500
Material	Kunststoff
Temperature range	-25 - 45
LED per meter	60
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	67.000 h
Suitable light source	





**VARDaflex Standard IP67 Reach25
Flex.LED Strip, 24V, IP67, 3000K**
Article nr.: 86550-V3

TECHNICAL DRAWING

