

VARDAflex Neon SVQ - 2500K S?-?? Flex.LEDStrip, 24V, UWW

Article nr.: S86167

Flexible LED Stripe sealed in UV-, chlorine-, salt water-, solventresistant white PVC · for indoor- and outdoor use, IP68 · Cuttable every 55,56 mm / 6 LEDs · Amount of LEDs per meter: 108 · LED pitch: 9,26 mm · Beam angle: 160° · CRI: >80 · Luminous flux per meter: 437 lm · Voltage: 24V DC · Power per Meter: 12 W · Lifetime L70: >= 36.000 h · Energy efficiency class: B · WxH in mm: 16 x 17 · Temperature range: -20 to +45°C · Processing temperature: +10 to +45°C · Maximum length per connection: 10 meter · Bending radius: 300 mm

TECHNICAL DATA

Unit Code	metre
BAR code	4012094061672
Housing colour	Weiss
Width	16.00 mm
Height	17.00 mm
LED colour	UWW ca. 2500K
Lightoutput per LED	4.05 lm
Lamp	Inklusive LED
IP rating	68
Voltage	24 V



VARDAflex Neon SVQ - 2500K S?-?? Flex.LEDStrip, 24V, UWW

Article nr.: S86167

TECHNICAL DATA

Material	Kunststoff
Temperature range	-20 - 45
LED per meter	108
Dimension of segments	55.56 mm
Energy efficiency class	B
CRI	≥ 80

