



VARDAflex Osmium TVQ 2700K - 5M- Rolle LED-Strip, 24V, 13W/m, IP65, 2700K

Article nr.: 79647

flexible LED Stripe sealed in UV- and · saltwater resistant white silicone · for indoor- and outdoor use, IP65 · · cuttable every 50 mm / 7 LEDs · amount of LEDs per meter: 140 · LED pitch: 7.14 mm · beam angle: 110° · CRI: >90 · luminous flux per meter: 470 lm · power per meter: 13 W · lifetime L70B50: >= 54,000 h · LxWxH in mm: 5,000 x 16 x 16 · · temperature range: -20 to +45°C · processing temperature: +10 to +45°C · maximum length per connection: 5 meter · bending diameter vertical: 130 mm · Delivery contents: 5 meter reel with 1 meter connection cable on both ends, · 2x silicon end caps

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094797472
Housing colour	Weiss
Length	5000.00 mm
Width	16.00 mm
Height	16.00 mm
LED colour	ca. 2700 K ultra warmweiß
Lightoutput per fixture	2350.00 lm
Lightoutput per LED	3.36 lm
Lamp	Inklusive LED





VARDAflex Osmium TVQ 2700K - 5M- Rolle LED-Strip, 24V, 13W/m, IP65, 2700K

Article nr.: 79647

TECHNICAL DATA

IP rating	65
Power	65 W
Psb	0,0 W
Current mA	2.708 mA
Voltage	24 V
Amount of LED	700
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
CRI	≥ 90
Lifetime L70B50	54.000 h
Lifetime L90B10	39.000 h





**VARDAflex Osmium TVQ 2700K - 5M-
Rolle LED-Strip, 24V, 13W/m, IP65,
2700K**

Article nr.: 79647

TECHNICAL DRAWING

