




VARDAflex 4inONE-72 - IP65 - 5M- Rolle Flex.LED Strip, 24V, IP65, RGBW 3000K, CRI80

Article nr.: 79513

flexible LED Strip with self adhesive backside, · for indoor and outdoor use, IP65 · not UV-resistant · can be separated every 83.33 mm or 6 LEDs · number of LEDs: 360 · LED pitch: 13.89 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 890 lm · luminous flux 3000K per meter: 391 lm · input voltage: 24 V DC · power per meter: 14.4 W · lifespan L70B50: >= 36,000 h · energy efficiency class: E · LxWxH in mm: 5,000 x 14 x 4.2 · · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection, 10 x silicone mounting bracket, · 20x screws, 1 x end cap closed, 1 x end cap feed, 1x 300 mm connection cable for soldering

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795133
Housing colour	Weiss
Length	5000.00 mm
Width	14.00 mm
Height	4.20 mm
LED colour	RGBW 3000K
Lightoutput per fixture	4450.00 lm
Lightoutput per LED	12.36 lm
Lamp	including LED





**VARDAflex 4inONE-72 - IP65 - 5M-
Rolle Flex.LED Strip, 24V, IP65, RGBW
3000K, CRI80**

Article nr.: 79513

TECHNICAL DATA

IP rating	65
Power	72 W
Psb	0,00 W
Current mA	3000 mA
Voltage	24 V
Amount of LED	360
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h
Suitable light source	

