




VARDAflex 3inONE-30 - IP65 - 5 Meter Rolle Flex. LED-Strip im Schlauch, IP65, RGB

Article nr.: 86548

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP65 · not UV-resistant · can be separated every 166.67 mm or 5 LEDs · number of LEDs: 150 · LED pitch: 33.33 mm · beam angle: 120° · CRI: - · luminous flux per meter: 205 lm · input: 24V DC · power per meter: 7.2 W · lifetime L70B50: >= 69,000 h · LxWxH in mm: 5,000 x 12 x 4 · Maximum length per connection: 5 meter. New connectors for greater length. · scope of delivery: 5 meter reel with 150 mm connecting cable and plug/socket at · each end, 1x socket with 150 mm connection cable, 1x plug as end cap, · 2x silicone cap with cable feed-through, 2x silicone cap closed, · 20x silicone fixing brackets

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094865485
Length	5000.00 mm
Width	12.00 mm
Height	4.00 mm
LED colour	RGB
Lightoutput per fixture	1025.00 lm
Lightoutput per LED	6.83 lm
Lamp	Inklusive LED
IP rating	65





VARDAflex 3inONE-30 - IP65 - 5 Meter Rolle Flex. LED-Strip im Schlauch, IP65, RGB

Article nr.: 86548

TECHNICAL DATA

Power	36 W
Psb	0,00 W
Current mA	1.500 mA
Voltage	24 V
Amount of LED	150
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	30
Dimension of segments	166.67 mm
Lifetime L70B50	69.000 h
Lifetime L90B10	35.000 h

