



**VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K**
Article nr.: 82207-V2

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 100 mm or 6 LEDs · Number of LEDs: 1.200 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · Lumen per meter: 400 lm · Voltage: 24V DC · Power per meter: 5 W · Lifetime L70B50: >= 50.000 h · energy efficiency class: G · LxWxH in mm: 20.000 x 10 x 1,6 · · Easy installation with solderless connector (optional). · Maximum length per connection: 20 meter. New connectors for greater length. · Delivery contents: 20 meter reel with connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094812076
Housing colour	Weiss
Length	20000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	UWW ca. 2700 K
Lightoutput per fixture	8000.00 lm
Lightoutput per LED	6.67 lm
Lamp	Inklusive LED





VARDAflex Eco Reach20 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K

Article nr.: 82207-V2

TECHNICAL DATA

IP rating	20
Power	100 W
Current mA	4.200 mA
Voltage	24 V
Amount of LED	1200
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	50.000 h





VARDAflex Eco Reach20 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K
Article nr.: 82207-V2

TECHNICAL DRAWING

