rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus Reach15, IP20 24V, 10W/m, 927, 15m

Article nr.: 82217-V2

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be seperated every 50 mm or 6 LEDs · number of LEDs: 1.800 · LED pitch: 8,33 mm · beam angle: 120° · CRI: >90 · IC module on board (constant current module) · lumen per meter: 807 lm · voltage: 24V DC · power per meter: 10 W · lifetime L70B50: >= 50.000 h · energy efficiency class: G · LxWxH in mm: 15.000 x 10 x 1,6 · · Easy installation with solderless connector (optional). · Maximum length per connection: 15 meter. New connectors for greater length. · Delivery contents: 15 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094812175
Housing colour	Weiss
Length	15000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	12105.00 lm
Lightoutput per LED	6.72 lm
Lamp	including LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus Reach15, IP20 24V, 10W/m, 927, 15m

Article nr.: 82217-V2

TECHNICAL DATA

IP rating	20
Power	150 W
Psb	0,00 W
Current mA	6300 mA
Voltage	24 V
Amount of LED	1800
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	50.00 mm
Energy ffficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h
Suitable light source	



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus Reach15, IP20 24V, 10W/m, 927, 15m

Article nr.: 82217-V2

TECHNICAL DRAWING

