rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 82418

flexible LED Strip with self adhesive backside, · for indoor use. · · Can be seperated every 100 mm or 7 LEDs · Number of LEDs: 350 · LED pitch: 14.28 mm · beam angle: 120° · CRI: >90 · Lumen per meter: 445 lm · Voltage: 24V DC · Power per meter: 4.8 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 8 x 2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 10 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094824185
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2225.00 lm
Lightoutput per LED	6.36 lm
Lamp	including LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 82418

TECHNICAL DATA

IP rating	20
Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	350
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	36.000 h
Lifetime L90B10	13.000 h
Suitable light source	



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 82418

TECHNICAL DRAWING

