




VARDaflex Eco Plus CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, 9, 6W/m, IP20, 3000K

Article nr.: 82475

flexible LED Strip with self adhesive backside, · for indoor use. · can be separated every 50 mm or 7 LEDs · number of LEDs: 700 · LED pitch: 7.14 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 906 lm · voltage: 24V DC · power per meter: 9.6 W · lifespan L70B50: >= 50,000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 8 x 1,4 · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094824758
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	1.40 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4530.00 lm
Lightoutput per LED	6.47 lm
Lamp	including LED





VARDAflex Eco Plus CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, 9, 6W/m, IP20, 3000K

Article nr.: 82475

TECHNICAL DATA

IP rating	20
Power	48 W
Psb	0,00 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h
Suitable light source	





VARDAflex Eco Plus CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, 9, 6W/m, IP20,
3000K

Article nr.: 82475

TECHNICAL DRAWING

