rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus, IP20 24V, 9, 6W/m, 927, 5m

Article nr.: 82477

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 50 mm or 7 LEDs · number of LEDs: 700 · LED pitch: 7.14 mm · beam angle: 120° · CRI: >90 · luminous flux per meter: 941 lm · voltage: 24V DC · power per meter: 9.6 W · lifespan L70B50: >= 50,000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 8 x 1.4 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094824772
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	1.40 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	4705.00 lm
Lightoutput per LED	6.72 lm
Lamp	including LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus, IP20 24V, 9, 6W/m, 927, 5m

Article nr.: 82477

TECHNICAL DATA

IP rating	20
Power	48 W
Psb	0,00 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h
Suitable light source	

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 Plus, IP20 24V, 9, 6W/m, 927, 5m

Article nr.: 82477

TECHNICAL DRAWING

