rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Standard - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84315

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be seperated every 125 mm or 6 LEDs · Number of LEDs: 240 · LED pitch: 20.83 mm · Beam angle: 120° · CRI: >80 · Luminous flux per metre: 352 lm · Voltage: 24 V DC · Power per metre: 3.5 W · Lifetime L70B50: >= 60,000 h · Energy efficiency class: F · LxWxH in mm: 5,000 x 8 x 2.2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel, 5 in-feeder connector (profi), · 1 direct connector (profi)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094843155
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.20 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	1760.00 lm
Lightoutput per LED	7.33 lm
Lamp	Inklusive LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Standard - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84315

TECHNICAL DATA

IP rating	20
Power	17,5 W
Current mA	729 mA
Voltage	24 V
Amount of LED	240
Temperature range	-20 - 45
LED per meter	48
Dimension of segments	125.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	60.000 h



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Standard - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84315

TECHNICAL DRAWING

