




VARDAflex COB R-to-R Plus - 5 Meter Rolle Flex.LEDStrip, 24V, 10, 5W/m, Innen, 4000K

Article nr.: 84338

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · can be separated every 50 mm or 24 LEDs · number of LEDs: 2400 · LED pitch: 2.08 mm · beam angle: 180° · CRI: >90 · luminous flux per metre: 1065 lm · voltage: 24 V DC · power per metre: 10,5 W · lifespan L70B50: >= 54,000 h · Energy efficiency class: F · LxWxH in mm: 5,000 x 8 x 2.2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094843384
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.20 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	5325.00 lm
Lightoutput per LED	2.22 lm
Lamp	including LED






VARDAflex COB R-to-R Plus - 5 Meter
Rolle Flex.LEDStrip, 24V, 10, 5W/m,
Innen, 4000K

Article nr.: 84338

TECHNICAL DATA

IP rating	20
Power	52,5 W
Psb	0,00 W
Current mA	2187 mA
Voltage	24 V
Amount of LED	2400
Temperature range	-20 - 40
LED per meter	480
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	54.000 h
Lifetime L90B10	20.000 h
Suitable light source	





VARDAflex COB R-to-R Plus - 5 Meter
Rolle Flex.LEDStrip, 24V, 10, 5W/m,
Innen, 4000K
Article nr.: 84338

TECHNICAL DRAWING

