rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 COB, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 84418

flexible LED Strip with self adhesive backside · for indoor use, IP20 · · can be seperated every 100 mm or 32 LEDs · number of LEDs: 1600 · LED pitch: 3.13 mm · Beam angle: 180° · CRI: >90 · Lumen per meter: 560 lm · Voltage: 24 V DC · Power per meter: 4.8 W · Lifespan L70B50: >= 54.000 h · energy efficiency class: F · LxWxH in mm: 5,000 x 8 x 1.9 · · Maximum length per connection: 5 metre. New connectors for greater length. · Delivery contents: 5 metre roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094844183
Length	5000.00 mm
Width	8.00 mm
Height	1.90 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2800.00 lm
Lightoutput per LED	1.75 lm
Lamp	including LED
IP rating	20

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 COB, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 84418

TECHNICAL DATA

Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	1600
Temperature range	-20 - 45
LED per meter	320
Dimension of segments	100.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	54.000 h
Lifetime L90B10	20.000 h
Suitable light source	



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



LED-Strip VARDAflex 90 COB, IP20 24V, 4, 8W/m, 940, 5m

Article nr.: 84418

TECHNICAL DRAWING

