


**VARDAflex Slim UWW 5M-R.****Flex.LEDStrip, 24V, Innen, 2700K CRI90**

Article nr.: 84603

flexible LED Strip with self adhesive backside, · for indoor use. · can be separated every 5 cm or 7 LEDs · number of LEDs: 700 · LED pitch: 7.14 mm · beam angle: 120° · CRI: >90 · lumen per meter: 918 lm · voltage: 24V DC · power per meter: 10 W · lifetime L70B50: >= 60.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 3.5 x 1.2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll with 300 mm connection cable

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094846033
Housing colour	Weiss
Length	5000.00 mm
Width	3.50 mm
Height	1.20 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	4590.00 lm
Lightoutput per LED	6.56 lm
Lamp	including LED






VARDAflex Slim UWW 5M-R.

Flex.LEDStrip, 24V, Innen, 2700K CRI90

Article nr.: 84603

TECHNICAL DATA

IP rating	20
Power	50 W
Psb	0,00 W
Current mA	2083 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	60.000 h
Lifetime L90B10	28.000 h
Suitable light source	





VARDAflex Slim UWW 5M-R.

Flex.LEDStrip, 24V, Innen, 2700K CRI90

Article nr.: 84603

TECHNICAL DRAWING

