rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

VARDAflex Mini Ultra WW 5M-R. Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84975

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 10 cm or 7 LEDs · number of LEDs: 350 · LED pitch: 14.29 mm · beam angle: 120° · CRI: >80 · IC module on board (constant current module) · lumen per meter: 1649 lm · voltage: 24V DC · power per meter: 15 W · lifetime L70B50: >= 60.000 h · energy efficiency class: F · LxWxH in mm: 5.000 x 5 x 1.5 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094849751
Housing colour	Weiss
Length	5000.00 mm
Width	5.00 mm
Height	1.50 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	8245.00 lm
Lightoutput per LED	23.55 lm
Lamp	Inklusive LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

VARDAflex Mini Ultra WW 5M-R. Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84975

TECHNICAL DATA

IP rating	20
Power	75 W
Current mA	3.125 mA
Amount of LED	350
Input voltage	24
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy ffficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	60.000 h

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

VARDAflex Mini Ultra WW 5M-R. Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84975

TECHNICAL DRAWING

