rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco Double CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82427

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 50 mm or 7 LEDs · number of LEDs: 700 · LED pitch: 7.14 mm · beam angle: 120° · CRI: >90 · lumen per meter: 1600 lm · voltage: 24V DC · power per meter: 19.2 W · lifetime L70: >= 36.000 h · LxWxH in mm: 5.000 x 10 x 1.5 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094224275
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	8000.00 lm
Lightoutput per LED	11.42 lm
Lamp	Inklusive LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco Double CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82427

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4.000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
CRI	≥ 90

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Eco Double CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82427

TECHNICAL DRAWING

